




WEST VISAYAS STATE UNIVERSITY
 Janiuay Campus
 Janiuay, Iloilo

REQUEST FOR QUOTATION
Tel. 330-3485 local. 132

Date : November 25, 2022
 Quotation No. : 2022-116
 Based on P.R. : 2022-134
 Approved Budget for the Contract (ABC) : **₱ 162,000.00**

Gentlemen:

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the back page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than December 5, 2022 in a sealed envelope.


 FLORENCIO L. CORDURA, JR., MAT, MATH
 Chair, BAC

- Note:
1. All entries must be typewritten or legibly handwritten.
 2. Delivery period within THIRTY (30) calendar days.
 3. Warranty shall be for a period of six (6) mos. For supplies & materials, one (1) year for equipment, From the date of acceptance by procuring entity.
 4. Price validity shall be for a period of ONE HUNDRED TWENTY (120) calendar days.
 5. ***Bidders shall submit photocopy of PhilGEPS Registration Certificate, Mayor's Permit and Omnibus Sworn Statement.***

Item No.	UNIT	ITEM DESCRIPTION	QTY.	UNIT PRICE	TOTAL
		Supply and Delivery for the Procurement of Various Equipment for the conduct of Research Study titled, "Biodiversity Data and Knowledge and Attitudes of Community Folks: Baseline for the Policy Enhancement and Development of Sustainable Biodiversity Program" - Re-posting			
1	unit	Handheld GPS Specification: Physical Dimension: 2.1" x 4.0" x 1.3" (5.4 x 10.3 x 3.3 cm) Display Size: 1.4" x 1.7" (3.5 x 4.4 cm); 2.2" diag (5.6 cm) Display Resolution: 240 x 320 pixels Display Type: 2.2" transfective, 65K color TFT Weight: 141.7 G (with batteries) Battery: 2AA batteries (not included); NiMH or Lithium recommended Battery Life: 25hours Water Rating: IPX7 Memory/History: 8GB High-Sensitivity Receiver: Yes Interface: USB Preloaded maps: Topoactive;routable Ability to add maps: Yes Basemap: Yes Automatic Routing (Turn by Turn Routing on Roads): Yes Map Segments: 3000 External Memory Storage: Yes Waypoints/Favorites/Locations: 2000 Routes: 200 Routes, 250 points/route;50points auto routing Track Log: 10,000 points, 200 saved tracks Geocaching-Friendly: Yes Hunt/Fish Calendar: Yes	1		

		Sun and Moon Information: Yes Branded with Complete Accessories			
2	unit	DO Meter Specification: Display: LCD size: 29 mm x 28 mm. Dual function LCD Circuit: Custom one-chip of microprocessor LSI circuit Measurement Range of Dissolved Oxygen: 0 to 20mg/L Range (air oxygen): 0 - 100% Temperature Range: 0 to 50°C Sensor Structure: Polarographic type Oxygen probe with an incorporated temperature sensor Temp. Compensation: 0 to 50°C Resolution (dissolved oxygen): 0.1mg/L Resolution (temperature): 0.1°C Accuracy (dissolved oxygen): ±0.4mg/L Accuracy (air oxygen): ±0.7% Accuracy (temperature): ±0.8°C/1.5°F Temperature compensation: 0 - 50°C, automatic adjustment Recall: Records maximum/minimum readings with recall Power off: Auto power off or manual off using push button Data hold: Freezes the display reading Sampling time: Approx. one second Operating temp: 0 - 50°C Operating humidity: Less than 80% RH Power supply: DC 1.5V battery (UM-4/AAA) x 4pcs Power current: Approx. DC 6.2 mA Weight: 390g Dimension: Main Instrument - 180x40x40mm, Oxygen probe-190mmx28mm Dia., Probe's cable length-4 meters Branded with Complete Accessories	1		
3	unit	Digital Pocket Thermometer Specification: Temperature Range: -40° to 450 °F (-40° to 232 °C) Accuracy: ± 2F° / ± 1C° Resolution: 0.1 ° LCD: 0.375 °H x 0.8125 ° W (9.5 mm x 20.6 mm) IPX7 Waterproof Rating Anti-microbial Enclosure and Sheath Adjustable Preset Temperature Alarm, Default at 140°F (60°C) Min/ Max/ Hold Modes Used to Test Dishwasher Rinse Temperature 4.75" (121 mm) Stainless Steel Stem Reduced Tip for <6 Second Response Time Protective Sheath & Pocket Clip Auto Shut-off After 10 minutes of Non-use Low Battery Indicator 1.5v #R44 Battery & Spare Included CE Certified, NSF, WEEE Marked, RoHS Compliant Guaranteed Accurate for Life Branded with Complete Accessories	1		
4	unit	Digital Saltmeter Specification: "Display: Large LCD display, 21.5 mm digit height. Max. display count no. 1999.." Measurement Range: 0 to 10% salt (%weight) Resolution 0.01 % salt accuracy: ±0.5 % salt value. Sampling Time: Approx. 0.4 seconds	1		

		Data Hold: freeze the measured pH value on the display Temperature Compensation: Automatic, 0 to 50 °C (32to122°F) Operating Temp.: 0 to 50 °C(32 to 122°F) Operating Humidity: Max. 80% RH Power Supply: DC 9V battery (heavy duty type)006P, MN1604(PP3) or equivalent. Power Current: Approx. DC 5 mA Weight: 270 g/0.60 LB (w/battery & electrode) "Dimension: Meter:200 x 68 x 30 mm (7.9 x 2.7 x 1.2 inch); Electrode : Round, 22 mm Dia. x 120 mm length." Branded with Complete Accessories			
5	unit	Digital pH Meter with pH electrode Specification: Display: 44mmx29mm, dual function LCD display Measurement : pH: 0 to 14 pH; mV: ±1999mV pH Electrode: Optional, any pH electrode with BNC Connector pH Calibration: pH7, pH 4, and pH 10 (3 points calibration) Input Impedance: 10 ¹² ohm Circuit: Custom one-chip of microprocessor LSI circuit Data Hold: Freeze the display reading Memory Recall: Maximum and Minimum Value Samplinh time of display: Approx. 1 second Power off: Auto/Manual Operating Temperature : 0 to 50°C Operating humidity: Less than 80% RH Power supply: 006P DC 9V battery (Alkaline or Heavy Duty type) Power current: Approx DC6 mA Weight: 200g/0.44LB Dimension: 135x60x33mm Branded with Complete Accessories	1		
6	unit	Fiber Glass Measuring Tape Specification: Length : 30m Blade Width : 12.7 mm Branded with Complete Accessories	1		
		<i>* All items are with free demonstration on how to use.</i>			
		X-X-X-X-X			
TOTAL LUMP SUM					

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Printed Name and Signature of Supplier

Tel. No. / Cellphone No./ E-mail address

Date

