




WEST VISAYAS STATE UNIVERSITY
 Janiuay Campus
 Janiuay, Iloilo

REQUEST FOR QUOTATION
Tel. 330-3485 local. 132

Date : January 31, 2023
 Quotation No. : 2022-115
 Based on P.R. : 2023-07
 Approved Budget for the Contract (ABC) : **P 203,000.00**

Gentlemen:

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the back page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than February 7, 2022 in a sealed envelope.


 FLORENCIO L. CORDURA, JR., MAT, MATH
 Chair, BAC

- Note:
1. All entries must be typewritten or legibly handwritten.
 2. Delivery period within TWENTY (20) calendar days.
 3. Warranty shall be for a period of six (6) mos. For supplies & materials, one (1) year for equipment, From the date of acceptance by procuring entity.
 4. Price validity shall be for a period of ONE HUNDRED TWENTY (120) calendar days.
 5. ***Bidders shall submit photocopy of PhilGEPS Registration Certificate, Mayor's Permit and Omnibus Sworn Statement.***

Item No.	UNIT	ITEM DESCRIPTION	QTY.	UNIT PRICE	TOTAL
		Supply and Delivery of Materials and Equipment for the New Campus Sound System			
1	unit	Mixer with Microphone input Specification: Line Input: Electronically balanced, Bandwidth: 10Hz to 60kHz ± 3dB, Distortion (THD&N): 0.01% at +4dB, 1kHz, Bandwidth 80kHz + 10dB to 40dBu, Max Output: +22dBu balanced, Aux Send max Out: +22dBu unbalanced +22dBu unbalanced, Control Room Out: 112dB all channels at Unity Gain, Power Supply: 110-240 VAC, 50-60Hz	1		
2	unit	Cross Over Specification: Number of Channels: 2, Modes: 2-way (Stereo), 3-way (Stereo), 4-way (Mono), Filter Types: Linkwitz-Riley, Crossover Frequencies – Stereo: Variable, Crossover Frequencies – Mono: Variable, Inputs: 2 x XLR, Outputs: 6 x XLR (2 x Low, 2 x Mid, 2 x High), Rack Spaces: 1U, HDW: 1.75" x 8.5" x 19", CD horn correction supplies constant-directivity compensation, High-quality components and exceptionally rugged construction ensure long life	1		
3	unit	Equalizer <ul style="list-style-type: none"> • Dual Band • Switchable boost/cut range of ±6 or ±15 dB • Servo balanced/unbalanced outputs • RF filtered inputs and outputs • XLR, Barrier Strip and ¼" TRS connectors • -12dB/ +12dB input gain range • 18dB/ octave 40Hz Bessel low-cut filter • Chassis/ Signal ground lift capability • Internal power supply transformer • Power-off hardware relays bypass with 2 second power-up delay 	1		

4	unit	Powered Speaker with stand Specification: Drivers: 15" Woofer 350 Watts, 1.35" Titanium Tweeter 50 Watts, Power: 400 Watts Continuous 800 Watts Peak, Freq Range: 40Hz to 20kHz, Input: Balanced XL	3		
5	unit	Powered Amplifier Specification: Output Power: 8 ohms, each channel, stereo (1kHz RMS) 650Wx2, Signal to Noise Ratio: >100dB, Residual Noise: <70dB, Input Sensitivity: 1.2V	1		
6	unit	Microphone Specification: Microphone Type: Dynamic , Polar Pattern: Cardioids, Frequency Response: 70Hz-15kHz, Output Impedance: 600 ohms, Color: Black, Connector: XLR,	2		
7	roll	Speaker Wire, Royal Cord, 14/2, 100M/roll	2		
8	pair	Male and Female XLR	12		
9	unit	Microphone Stand with Wireless Holder	2		
10	roll	Stranded Cable, 100M/roll	2		
11	roll	Flat Cord, #18, 100M/roll	2		
12	pc	Baby Jack	1		
		X-X-X-X-X			
TOTAL LUMP SUM					

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Printed Name and Signature of Supplier

Tel. No. / Cellphone No./ E-mail address

Date