




WEST VISAYAS STATE UNIVERSITY
 Janiuay Campus
 Janiuay, Iloilo

REQUEST FOR QUOTATION
Tel. 330-3485 local. 132

Date : October 19, 2022
 Quotation No. : 2022-95
 Based on P.R. : 2022-111
 Approved Budget for the Contract (ABC) : **₱ 162,000.00**

Gentlemen:

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the back page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than October 26, 2022 in a sealed envelope.


 FLORENCIO L. CORDURA, JR., MAT, MATH
 Chair, BAC

- Note:
1. All entries must be typewritten or legibly handwritten.
 2. Delivery period within TWENTY (20) calendar days.
 3. Warranty shall be for a period of six (6) mos. For supplies & materials, one (1) year for equipment, From the date of acceptance by procuring entity.
 4. Price validity shall be for a period of ONE HUNDRED TWENTY (120) calendar days.
 5. *Bidders shall submit photocopy of PhilGEPS Registration Certificate, Mayor's Permit and Omnibus Sworn Statement.*

Item No.	UNIT	ITEM DESCRIPTION	QTY.	UNIT PRICE	TOTAL
		Supply and Delivery for the Procurement of Various Equipment for the conduct of Research Study titled, "Biodiversity Data and Knowledge and Attitudes of Community Folks: Baseline for the Policy Enhancement and Development of Sustainable Biodiversity Program"			
1	unit	Handheld GPS Specification: Physical Dimension: 2.1" x 4.0" x 1.3" (5.4 x 10.3 x 3.3 cm) Display Size: 1.4" x 1.7" (3.5 x 4.4 cm); 2.2" diag (5.6 cm) Display Resolution: 240 x 320 pixels Display Type: 2.2" transfective, 65K color TFT Weight: 5 oz (141.7 g) with batteries Battery: 2AA batteries; NiMH or Lithium Battery Life: 25hours Water Rating: IPX7 Memory/History: 16GB High-Sensitivity Receiver: / Interface: USB Preloaded maps: Topoactive and routable Ability to add maps: / Basemap: / Memory Storage and Power Capacity: microSD™ card Waypoints/Favorites/Locations: 2000 Routes: 200 Track Log: 10,000 points, 200 saved tracks Automatic Routing (Turn by Turn Routing on Roads): Geocaching-Friendly: / Hunt/Fish Calendar: / Sun and Moon Information: / Branded with Complete Accessories	1		

2	unit	<p>DO Meter Specification: Measurement Range of Dissolved Oxygen: 0 to 20mg/L Temperature Range : 0 to 50 ° C Sensor Structure: Polarographic type Oxygen probe with temperature sensor Display: Dual function LCD, 29mm x 28mm Circuit: Custom one-chip microprocessor LSI circuit Range (air oxygen): 0 - 100% Resolution (dissolved oxygen): 0.1ml/L Resolution (air oxygen): 0.1% Resolution (temperature): 0.1°C Accuracy (dissolved oxygen): ±0.4mg/L Accuracy (air oxygen): ±0.7% Accuracy (temperature): ±0.8°C Temperature compensation: 0 - 50°C, automatic adjustment Recall: Records maximum/minimum readings with recall Power off: Auto power off or manual off using push button Data hold: Freezes the display reading Sampling time: Approx. one second Operating temp: 0 - 50°C Operating humidity: 0 - 50°C Power supply: 4 x AAA batteries Power current: Approx. DC 6.2 mA Weight: 390g Protection: IP67 (0 - 30°C), IP65 (30 - 50°C) Branded with Complete Accessories</p>	1		
3	unit	<p>Digital Pocket Thermometer Specification: Range: -40 to 500°F (-40 to 260°C) Accuracy: ± 1°F (±0.5°C) for Full range Resolution: 0.1 °F (0.1 °C) Stem Length: 5" (127mm) Stainless Steel Battery: 1 x Cr2032 Extra Large LCD 1.5mm diameter probe Waterproof Branded with Complete Accessories</p>	1		
4	unit	<p>Digital Saltmeter Specification: Certification:CE "Display: Large LCD display, 21.5 mm digit height.Max display count no.1999... Max. display count no. 1999" Display Hold:To feeze the measured pH value on the display. Temperature Compensation: Automatic,0 to 50°C Measurement Range: 0 to 10% salt (%weight) Automatic Temperature Compensation for the probe Operating Temp.: 0 to 50 °C(32 to 122°F) Operating Humidity: Max. 80% RH Resolution 0.01 % salt accuracy: ±0.5 % salt value. Sampling Time: 0.4 seconds Power Supply: DC 9V battery (heavy duty type)006P, MN1604(PP3) or equivalent. Power Current: Approx. DC 5 mA Weight: 270 g/0.60 LB (w/battery & electrode) Dimension: Meter:200 x 68 x 30 mm (7.9 x 2.7 x 1.2 inch); Electrode :Round, 22 mm Dia. x 120 mm length. Branded with Complete Accessories</p>	1		

5	unit	Digital pH Meter with pH electrode Specification: Display: 20 x 28mm Measurement Range : 0 to 14 pH; ±1999mV Resolution: 0.01 pH Accuracy: ± 0.07 pH (pH 5 to pH9); ± 0.1 pH (pH 4 to pH 4.9, pH 9.1 to pH 10); ± 0.2 pH (pH 1 to pH 3.9, pH 10.1 to pH 13). Input impedance: 10-12 ohms Temperature compensation: Not necessary to make adjustment Sampling time: Approx 0.8 second Hold function: To freeze the display reading value Calibration method: Auto calibration, pH 7, pH 4 (or pH 10)* pH electrode connector: BNC connector Operating Temperature : 0 to 50°C (32 to 122°F) Operating humidity: Less than 80% RH Power supply: DC 1.5V battery (UM-4/AAA) Power consumption: Approx 4.8mA Dimensions: Meter 180 x 40 x 32mm; Electrode 12 x 150mm; Electrode cable 750mm Weight: 220g (0.48lb) including electrode Branded with Complete Accessories	1		
6	unit	Steel Measuring Tape Specification: Length : 30m Width: 12.7 mm Blade Width : 12.7 mm Imperial and Metric Blade Material: Steel Branded with Complete Accessories	1		
		* All items are with free demonstration on how to use.			
		X-X-X-X-X			
TOTAL LUMP SUM					

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Printed Name and Signature of Supplier

Tel. No. / Cellphone No./ E-mail address

Date