



WEST VISAYAS STATE UNIVERSITY
 Janiuay Campus
 Janiuay, Iloilo

REQUEST FOR QUOTATION
Tel. 320-0647

Date : June 5, 2024
 Quotation No. : 2024-57
 Based on P.R. : 2024-61
 Approved Budget for the Contract (ABC) : **₱ 63,119.20**

Gentlemen:

Please quote your lowest price on the item/s listed below, subject to the General Conditions, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than June 13, 2024 at 10:00 A.M. in a sealed envelope.


 FLORENCIO L. CORDURA, JR., MAT, MATH
 Chair, BAC

- Note:
1. All entries must be typewritten or legibly handwritten.
 2. Delivery period within THIRTY (30) calendar days.
 3. Warranty shall be for a period of six (6) mos. for supplies & materials, one (1) year for equipment, from the date of acceptance by procuring entity.
 4. Price validity shall be for a period of ONE HUNDRED TWENTY (120) calendar days.
 5. *Bidders shall submit photocopy of PhilGEPS Registration Certificate, Mayor's Permit and Omnibus Sworn Statement.*

Item No.	UNIT	ITEM DESCRIPTION	QTY.	UNIT PRICE	TOTAL
Supply and Delivery of IT Peripherals					
1	unit	10/100/1000 Base-T to 1000Base-SX/LX Media Converter Single-Mode Fiber (Auto MDI/MDIX), Full Duplex, Chassis Mountable, UTP Category 5, 5e <ul style="list-style-type: none"> • Standard: IEEE802.3 & IEEE802.3z & 802.3ab • Interface: 1 x RJ-45 connector / 1 x SFP Slot 	4		
2	unit	SFP Module 1000BASE-LX Single-mode, SFP Transceiver up to 10Km Compatible with Dlink DGS 1210 28P Switch	4		
3	roll	Fiber Cable Single Mode Core/Cladding Size: 9/125 um Wave lengths: 1310nm, 1550nm Laser Sources Bandwidth: 100,000 GHz	1		
4	box	305 Cat5e UTP Ethernet Cable UTP-104 24AWG Solid (Grey) Cat5e UTP Cable supports Gigabit Ethernet (1000 Base-T) standard	3		
5	unit	Fiber of optic toolkit Fiber cleaver .Applicable bare fiber diameter: 125um 2.Applicable fiber core number: single core Optical power meter 1. Wavelength range: 800~1700nm 2.Connector: FC/SC/ST (optional) 3.Uncertainty: ±5% 4.Standard wavelength (nm): 850/1300/1310/1490/1550/1625 5.	1		

6	unit	Butterfly Connector Fiber Optic Fast Connector Sc APC Upc Quick Connector for FTTH Drop Cable Field Termination	10		
7	unit	Access Point 802.11ac Wave 1 WiFi technology Dual omnidirectional antennae with 2x2 MIMO functionality 5 GHz/867 Mbps throughput rate/ 2.4 GHz /300 Mbps throughput rate WiFi standards 802.11a/b/g/n/ac Advanced QoS Per-user rate limiting	2		
8	unit	Wifi Router Standards: Wi-Fi 5, IEEE 802.11ac/n/a 5 GHz, IEEE 802.11n/b/g 2.4 GHz WiFi Range: 4× Fixed High-Performance Antennas WiFi Capacity: Medium Dual-Band, MU-MIMO Working Modes: Router Mode , Access Point Mode Ethernet Ports: 1× Gigabit WAN Port, 4× Gigabit LAN Ports SECURITY: WiFi Encryption WPA, WPA2, WPA3, WPA/WPA2-Enterprise (802.1x) Network Security SPI Firewall	5		
		X-X-X-X-X			
TOTAL LUMP SUM					

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Printed Name and Signature of Supplier

Tel. No. / Cellphone No./ E-mail address

Date