




WEST VISAYAS STATE UNIVERSITY  
 Janiuay Campus  
 Janiuay, Iloilo

**REQUEST FOR QUOTATION**  
**Tel. 531-8923 local. 132**

Date : October 21, 2021  
 Quotation No. : 2021-59  
 Based on P.R. : 2021-73  
 Approved Budget for the Contract (ABC) : **₱ 210,000.00**

Gentlemen:

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the back page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than November 2, 2021 at **10:00 A.M.** in a sealed envelope.

  
 FLORENCIO L. CORDURA, JR., MAT, MATH  
 Chair, BAC

- Note:
- All entries must be typewritten or legibly handwritten.
  - Delivery period within TWENTY (20) calendar days.
  - Warranty shall be for a period of six (6) mos. For supplies & materials, one (1) year for equipment, From the date of acceptance by procuring entity.
  - Price validity shall be for a period of ONE HUNDRED TWENTY (120) calendar days.
  - Bidders shall submit authenticated photocopy of PhilGEPS Registration Certificate, Mayor's Permit and Omnibus Sworn Statement.

Item No.	UNIT	ITEM DESCRIPTION	QTY.	UNIT PRICE	TOTAL
<b>Procurement of Electricity Laboratory Equipment</b>					
1	unit	Oscilloscope Specifications: 200 MHz, 2 Channel Oscilloscope, 2 analog channels, 50 Ohm input impedance (standard), Vertical range: 500 µV/div ~ 10 V/div, Real-time sample rate: up to 1 GSa/s on both channels, Memory depth: up to 28 Mpts on both channels, Waveform capture rate: up to 50,000 wfms/s, Real-time hardware waveform recording, playback, and analysis of up to 65,000 captured frames, Various serial trigger and decode (RS232/UART, I2C, SPI, CAN and LIN), Complete connectivity: USB DEVICE, USB Host, LAN, and optional GPIB, 8-inch WVGA (800x480), 256-level intensity grading display, Brand New, with complete standard accessories	2		
2	unit	Programmable Logic Control Specification: Number of inputs: 8 (digital) Input type: Digital Voltage Category: 24 V DC Output Type: Digital Number of Outputs: 4 (Digital) Network Type: USB Communication Port Type: RS485 Program Capacity: 64 kB Programming Interface: Simatic PC/PC Memory: 8 (load) MB, 64 (Integrated) kB Width: 80mm Mounting Type: DIN Rail, Wall Mount Length: 125 mm Output Current: 500 mA Depth: 130 mm Minimum Operating Temperature: 0 deg Cel Dimension: 125x80x130 mm Programming Language Used: FBD, GRAPH, Hi Graph, LAD, SCL, STL Maximum Operating Temperature: +60 deg Cel, Brand New, with complete accessories  X-X-X-X-X	1		
<b>TOTAL LUMP SUM</b>					

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Printed Name/Signature of Supplier

Tel. No. / Cellphone No./ E-mail address

Date